



|                             |   |
|-----------------------------|---|
| <b>Product Type:</b>        | Ultra High Tack Woven Polyethylene<br>Multi-Purpose All Weather Tape  |
| <b>Colour:</b>              | Translucent   |
| <b>Roll Size:</b>           | 6mm to 1100mm in 20m Lengths  |
| <b>Adhesive:</b>            | Acrylamide  |
| <b>Description:</b>         | A woven UV stabilised Polyethylene film coated with a high coat weight, UV Stabilised pressure sensitive acrylamide adhesive.   |
| <b>Application:</b>         | Designed for the strengthening and repair of coated woven fabrics. A premium repair tape for indoor & outdoor applications where a strong but flexible backing is required. Suitable for use on PVC backed surfaces where long-term waterproof and air tight seals are required. Supplied on a release liner, it is ideal for converting into repair patches. |
| <b>Technical Details:</b>   | Gauge: 0.50mm<br>Adhesion to Steel: 9.2 N/cm<br>Service Temperature: -5°C to 80°C<br>Storage Temperature: 15°C to 25°C<br>Shelf Life: 12 Months   |
| <b>Surface Preparation:</b> | The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.   |
| <b>Storage:</b>             | Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.   |

**DISCLAIMER:**

**Values:** All values presented have been determined by standard test methods and are average values only.

**Recommendations:** Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

**Warranty:** We can only warranty our products to the level that they are consistent with our Product Information Sheet values

**BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.**