



**Product Type:** Double Sided Foamed Acrylic - Bonding Tape

**Colour:** White

**Roll Size:** 6mm to 930mm in 33m Lengths

**Adhesive:** Acrylic Foamed LSE

**Description:** A White 0.6mm Foamed Acrylic Tape designed for applications where a high initial tack and very high permanent bond is required. It has a high performance foamed acrylic adhesive coated both sides with a special low surface energy (LSE) acrylic adhesive. It is plasticiser and UV resistant, giving good ageing properties. It is on a green plastic release liner suitable for die cutting.

**Application:** For structural bonding of metals and plastics. Typical applications include: signage, display, shopfitting, trim mounting and badge/nameplate mounting. Particularly for applications bonding dissimilar materials where differential expansion and contraction may be encountered.

**Technical Details:**

Gauge:	0.60mm
Elongation at Break:	1000%
180° Peel adhesion:	
After 15 Mins @ 23°C Stainless Steel	15.9 N/cm
After 24 Hours @ 23°C Stainless Steel	19.0 N/cm
After 24 Hours @ 23°C Polypropylene	14.9 N/cm
Service Temperature:	-30°C to 90°C
Short Term Temperature:	100°C
Shelf Life:	12 Months

**Surface Preparation:** The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

**Storage:** Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

**DISCLAIMER:**

**Values:** All values presented have been determined by standard test methods and are average values only.

**Recommendations:** Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

**Warranty:** We can only warranty our products to the level that they are consistent with our Product Information Sheet values

**BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.**